Sealing arrangement for a movable window pane

Patent number:

Publication date:

1998-04-03

Inventor: Applicant:

BRUEHL GISBERT (DE); KRAUSE FRITZ (DE) METZELER AUTOMOTIVE PROFILES (DE)

Classification:

- International:

- european:

B86J10/00C3; B80J10/00D; B80J10/00D5; B60J10/00D7B; B80J10/04; B80J10/04B

Application number: EP19950115075 19950925 Priority number(s): DE19944435088 19940930

Also published as:

EP0704597 (A2) EP0704597 (A3)

DE4435088 (A1)

Cited documents:


EP0282919

DE8908394U EP0421316

Report a data error here

Abstract of EP0704597

The seal (10) is extruded and fixed to the window frame (15), with elastic sealing portions (22,25) on inside and outside. An extruded shaft seal (10b) is mounted at the shaft opening (13a), and has elastic portions (22,25,27) bearing against the pane on inside and outside. The seal is in one piece, having a common basic profiled portion for frame and shaft sealing and equipped with tips (27,28). At the shaft seal (10b) it has a recess (30) for the shaft opening (13c). The basic portion (17) cast have mounting flanges (18,19) spaced apart, for fixing to flanges on the bodywork, and which can contain U-section metal inserts. The sealing portion bearing against the inside of the pane can contain a hollow space (23).



Data supplied from the esp@cenet database - Worldwide

BEST AVAILABLE COPY